



SUPERFY INDUSTRIAL LIMITED

MATERIAL SAFETY DATA SHEET

(REFRIGERANT GAS R22)

1.CHEMICAL PRODUCT/COMPANY IDENTIFICATION

PRODUCT NAME: R22

OTHER/GENERIC NAMES: R-22, HCFC-22

PRODUCT USE: Refrigerant

MANUFACTURER:

SUPERFY INDUSTRIAL LIMITED.

Add: Quzhou Economy Develop Area, Quzhou City, Zhejiang Province, China

2.COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME CAS NUMBER WEIGHT%

Chlorodifluoromethane 75-45-6 100

Trace impurities and additional material names not listed above may also appear in Section 14 toward the end of the MSDS.

These materials may be listed for local "Right-To-Know" compliance and for other reasons.

3.PHYSICAL AND CHEMICAL PROPERTIES

EMERGENCY OVERVIEW: Colorless, volatile liquid with ethereal and faint sweetish odor.

Non-flammable material. Overexposure may cause dizziness and loss of concentration. At higher levels, CNS depression and cardiac arrhythmia may result from exposure. Vapors displace air and can cause asphyxiation in confined spaces. At higher temperatures, (>250 C), decomposition products may include Hydrofluoric Acid (HF) and carbonyl halides such as phosgene.

POTENTIAL HEALTH HAZARDS

SKIN: Irritation would result from a defatting action on tissue. Liquid contact could cause frostbite.

EYES: Liquid contact can cause severe irritation and frostbite. Mist may irritate.

INHALATION: R 22 is low in acute toxicity in animals. When oxygen levels in air are reduced to 12–14% by displacement, symptoms of asphyxiation, loss of coordination, increased pulse rate and deeper respiration will occur. At high levels, cardiac arrhythmia may occur.

INGESTION: Ingestion is unlikely because of the low boiling point of the material. Should it occur,

discomfort in the gastrointestinal tract from rapid evaporation of the material and consequent evolution of gas would result.

Some effects of inhalation and skin exposure would be expected.

DELAYED EFFECTS: None known

Ingredients found on one of the OSHA designated carcinogen lists are listed below.

INGREDIENT NAME NTP STATUS IARC STATUS OSHA LIST

No ingredients listed in this section

4.FIRE FIGHTING MEASURES

SKIN: Promptly flush skin with water until all chemical is removed. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. Get medical attention if symptoms persist.

EYES: Immediately flush eyes with large amounts of water for at least 15 minutes (in case of frostbite water should be lukewarm, not hot) lifting eyelids occasionally to facilitate irrigation. Get medical attention if symptoms persist.

INHALATION: Immediately remove to fresh air. If breathing has stopped, give artificial respiration. Use oxygen as required, provided a qualified operator is available. Get medical attention. Do not give epinephrine (adrenaline).

INGESTION: Ingestion is unlikely because of the physical properties and is not expected to be hazardous. Do not induce vomiting unless instructed to do so by a physician.

ADVICE TO PHYSICIAN: Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions.

5.HAZARDS IDENTIFICATION

FLAMMABLE PROPERTIES

FLASH POINT: Gas, not applicable per DOT regulations

FLASH POINT METHOD: Not applicable

AUTOIGNITION TEMPERATURE: Unknown

UPPER FLAME LIMIT (volume% in air): None

LOWER FLAME LIMIT (volume% in air): None

Based on ASHRAE Standard 34 with match ignition

FLAME PROPAGATION RATE (solids): Not applicable

OSHA FLAMMABILITY CLASS: Not applicable

EXTINGUISHING MEDIA:

Use any standard agent – choose the one most appropriate for type of surrounding fire (material

itself is not flammable)

UNUSUAL FIRE AND EXPLOSION HAZARDS:

R 22 is not flammable at ambient temperatures and atmospheric pressure. However, this material will become combustible when mixed with air under pressure and exposed to strong ignition sources.

Contact with certain reactive metals may result in formation of explosive or exothermic reactions under specific conditions (e.g. very high temperatures and/or appropriate pressures).

SPECIAL FIRE FIGHTING PRECAUTIONS/INSTRUCTIONS:

Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool.

6.FIRST AID MEASURES

IN CASE OF SPILL OR OTHER RELEASE: (Always wear recommended personal protective equipment.)

Evacuate unprotected personnel. Protected personnel should remove ignition sources and shut off leak, if without risk, and provide ventilation. Unprotected personnel should not return until air has been tested and determined safe, including lowlying areas.

7.ACCIDENTAL RELEASE MEASURES

NORMAL HANDLING: (Always wear recommended personal protective equipment.)

Avoid breathing vapors and liquid contact with eyes, skin or clothing. Do not puncture or drop cylinders, expose them to open flame or excessive heat. Use authorized cylinders only. Follow standard safety precautions for handling and use of compressed gas cylinders.

R 22 should not be mixed with air above atmospheric pressure for leak testing or any other purpose.

STORAGE RECOMMENDATIONS:

Store in a cool, well-ventilated area of low fire risk and out of direct sunlight. Protect cylinder and its fittings from physical damage. Storage in subsurface locations should be avoided. Close valve tightly after use and when empty.

8.HANDLING AND STORAGE

ENGINEERING CONTROLS:

Provide local ventilation at filling zones and areas where leakage is probable. Mechanical (general) ventilation may be adequate for other operating and storage areas.

PERSONAL PROTECTIVE EQUIPMENT**SKIN PROTECTION:**

Skin contact with refrigerant may cause frostbite. General work clothing and gloves (leather) should provide adequate protection. If prolonged contact with the liquid or gas is anticipated, insulated gloves constructed of PVA, neoprene or butyl rubber should be used. Any contaminated clothing should be promptly removed and washed before reuse.

EYE PROTECTION:

For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear chemical safety goggles.

RESPIRATORY PROTECTION:

None generally required for adequately ventilated work situations. For accidental release or non-ventilated situations, or release into confined space, where the concentration may be above the PEL of 1,000 ppm, use a self-contained, NIOSH - approved breathing apparatus or supplied air respirator. For escape: use the former or a NIOSH-approved gas mask with organic vapor canister.

ADDITIONAL RECOMMENDATIONS:

Where contact with liquid is likely, such as in a spill or leak, impervious boots and clothing should be worn. High doselevel warning signs are recommended for areas of principle exposure. Provide eyewash stations and quick-drench shower facilities at convenient locations. For tank cleaning operations, see OSHA regulations, 29 CFR 1910.132 and 29 CFR 1910.133.

EXPOSURE GUIDELINES**INGREDIENT NAME ACGIH TLV OSHA PEL OTHER LIMIT**

Chlorodifluoromethane 1000 ppm TWA(8hr)

1000 ppm TWA(8hr)

None

* = Limit established by Honeywell.

** = Workplace Environmental Exposure Level (AIHA).

*** = Biological Exposure Index (ACGIH).

OTHER EXPOSURE LIMITS FOR POTENTIAL DECOMPOSITION PRODUCTS:

Hydrogen Fluoride: ACGIH TLV = 3 ppm ceiling

9.EXPOSURE CONTROLS/PERSONAL PROTECTION

APPEARANCE: Clear, colorless liquid and vapor

PHYSICAL STATE: Gas at ambient temperatures

MOLECULAR WEIGHT: 86.45

CHEMICAL FORMULA: CHClF₂

ODOR: Faint ethereal odor

SPECIFIC GRAVITY (water = 1.0): 1.21 @ 21.1 C (70 F)

SOLUBILITY IN WATER (weight%): 0.3 wt% @ 25 C and 1 atmosphere

pH: Neutral

BOILING POINT: -40.8 C (-41.40 F)

FREEZING POINT: -160 C (-256 F)

VAPOR PRESSURE: 136.1 psia @ 70 F

311.4 psia @ 130 F

VAPOR DENSITY (air = 1.0): 3.0

EVAPORATION RATE: >1 **COMPARED TO:** CCl₄ = 1

% VOLATILES: 100

FLASH POINT: Not applicable

(Flash point method and additional flammability data are found in Section 5.)

10. STABILITY AND REACTIVITY

NORMALLY STABLE? (CONDITIONS TO AVOID):

The product is stable.

Do not mix with oxygen or air above atmospheric pressure. Any source of high temperature, such as lighted cigarettes, flames, hot spots or welding may yield toxic and/or corrosive decomposition products.

INCOMPATIBILITIES:

(Under specific conditions: e.g. very high temperatures and/or appropriate pressures) – Freshly abraded aluminum surfaces (may cause strong exothermic reaction). Chemically active metals: potassium, calcium, powdered aluminum, magnesium and zinc.

HAZARDOUS DECOMPOSITION PRODUCTS:

Halogens, halogen acids and possibly carbonyl halides.

HAZARDOUS POLYMERIZATION:

Will not occur.

11. TOXICOLOGICAL INFORMATION

IMMEDIATE (ACUTE) EFFECTS:

LC₅₀ : 4 hr. (rat) - \geq 300,000 ppm

Cardiac Sensitization threshold (dog) – 50,000 ppm

DELAYED (SUBCHRONIC AND CHRONIC) EFFECTS:

Subchronic inhalation (rat) NOEL - 10,000 ppm

Not teratogenic

Not mutagenic in *in-vitro* or *in-vivo* tests

OTHER DATA:

Lifetime exposure of male rats was associated with a small increase in salivary gland fibrosarcomas.

12. ECOLOGICAL INFORMATION

Degradability (BOD): R 22 is a gas at room temperature; therefore, it is unlikely to remain in water.
Octanol Water Partition Coefficient: Unknown

13.DISPOSAL CONSIDERATIONS

RCRA

Is the unused product a RCRA hazardous waste if discarded?

Not a hazardous waste.

14.TRANSPORTATION INFORMATION

ROAD TRANSPORTATION

UN No.: 1018
Class: 2.2
ERG No.: 126
Hazchem warning: 2 C Non-flammable gas

STATE RIGHT-TO-KNOW

In addition to the ingredients found in Section 2, the following are listed for state right-to-know purposes.

INGREDIENT NAME WEIGHT% COMMENT

No ingredients listed in this section

ADDITIONAL REGULATORY INFORMATION:

R 22 is subject to U.S. Environmental Protection Agency Clean Air Act Regulations at 40 CFR Part 82.

WARNING:

Do Not vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any residual must be recovered.

Contains Chlorodifluoromethane, an HCFC substance which harms public health and the environment by destroying ozone in the upper atmosphere. Destruction of the ozone layer can lead to increased ultraviolet radiation which, with excess exposure to sunlight, can lead to an increase in skin cancer and eye cataracts.

WHMIS CLASSIFICATION:

This product has been evaluated in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

15.OTHER INFORMATION

The information given correspond to the current state of our knowledge and experience of the

product, and is not exhaustive. This applies to product that confirms to the specification, unless otherwise stated. In the case of combinations and mixtures one must make that no new dangers can arise. In any case, the user is not exempt from observing all legal, administrative and regulatory procedures relating to the product, personal hygiene, and protection of human welfare and environment.

Responsibility for MSDS: MSDS Coordinator

SUPERFY INDUSTRIAL LIMITED

Add: No. Quzhou Economy Develop Area, Quzhou City ,Zhejiang Province, China

Indicates updated section.

End of MSDS